

Zebra® 110PAX4™ 170PAX4™



PAX4™ Print Engines Deliver Superior Performance and Reliability

The 110PAX4 and the 170PAX4 print engines are the performance leaders in mission-critical print-and-apply applications. With increased throughput and enhanced connectivity, including wireless and Ethernet, along with all-metal construction and outstanding print quality, *PAX4* print engines deliver outstanding value, reliability, and durability.

Better Than Ever for High-Volume Needs

With improved serviceability, faster first-label-out time, and a fully functional real-time clock, the *PAX4* print engines deliver what it takes to make print-and-apply solutions super performers. European voltage requirements are now met with the 28V I/O option.

Real-time Connectivity and Control

Reduce downtime and increase productivity. Using advanced ZebraLink™ Solutions, *PAX4* print engines offer instant status alert messages and centralized control, allowing you to troubleshoot quickly and keep production lines moving.

802.11 b/g Wireless with Tethered Antenna

When equipped with ZebraNet® Internal Wireless Plus, *PAX4* supports the latest wireless security and authentication protocols. Featuring an integrated radio card, and a tethered antenna for added flexibility in maximizing wireless reception, *PAX4* stays connected to keep your business moving forward.



Designed for high-speed, high-throughput applications, both the 110PAX4 (for 4-inch printing) and the 170PAX4 (for print widths up to 6 inches wide) are ideal for print/apply systems including:

- Mission-critical industrial applications
- High-volume product, carton, case, and pallet labeling
- Packaging



Specifications at a Glance*

110PAX4

Print Specifications

Print Width

4.1"/104 mm

Print Length

Maximum non-continuous media: 39"/990 mm
Maximum continuous media: 100"/2540 mm

Physical Characteristics

- Width: 9.6"/245 mm
- Height: 11.8"/300 mm
- Depth: 16.4"/417 mm
- Weight: 36.5 lbs./15.6 kg

Media Characteristics

Media Width (label and liner)

0.625"/16 mm to 4.5"/114 mm

Media Thickness (label and liner)

0.0058"/0.148 mm to 0.010"/0.254 mm

Media Types

Continuous, die-cut or black mark

Ribbon Characteristics

Outside Diameter

4.0"/101.6 mm O.D

Standard Length

2,955/900 m

Ratio

Ribbon is recommended to be at least as wide as media

Ribbon Setup

Ribbon wound coated-side out

Core I.D.

1.0"/25.4 mm I.D. core

170PAX4

Printer Specifications

Print Width

6.6"/168 mm

Print Length

Maximum non-continuous media: 39"/990 mm
Maximum continuous media: 150"/3810 mm

Physical Characteristics

- Width: 9.6"/245 mm
- Height: 11.8"/300 mm
- Depth: 18.3"/465 mm
- Weight: 35.5 lbs./16.1 kg

Media Characteristics

Media Width (label and liner)

3.0"/76 mm to 7.1"/180 mm

Media Thickness (label and liner)

.003"/.076 mm to .012"/305 mm

Media Types

Continuous, die-cut or black mark

Ribbon Characteristics

Outside Diameter

4.0"/101.6 mm O.D

Standard Length

2,955/900 m

Ratio

Ribbon is recommended to be at least as wide as media

Ribbon Setup

Ribbon wound coated-side out

Core I.D.

1.0"/25.4 mm I.D. core

Standard Features

- Resolution:
 - 203 dpi/8 dots per mm;
 - 300 dpi/12 dots per mm
- Memory: 10 MB DRAM; 2 MB non-volatile Flash
- Print methods: Thermal transfer or direct thermal
- Print Speed: 12"/305 mm per second (203 dpi)
8"/203 mm per second (300 dpi)
- Media Sensors: Transmissive and reflective
- Orientation: Right-hand or left-hand
- Industrial all-metal construction
- 10 MB DRAM
- 2 MB non-volatile Flash memory
- Applicator interface
- Multilingual backlit LCD
- Enhanced Alert notification—monitors
- printhead condition
- Multi-level Element Energy Equalizer™ (E³) for superior print quality
- 32-bit 133 MHz RISC processor
- Zebra printer driver for Windows® 3.X and Windows 95/98/NT/2000
- Real-time clock
- XML-Enabled printing

Operating Characteristics

Environmental (Thermal Transfer)

- Operating Temp.
 - 40° F/5° C to 104° F/40° C
- Storage Temp.
 - 40° F/-40° C to 160° F/71° C
- Operating Humidity
 - 20% to 95% non-condensing R.H.
- Storage Humidity
 - 5% to 95% non-condensing R.H.

Electrical

Universal power supply with power-factor correction 90-264 VAC, 48-62 Hz

Agency Approvals

UL-60950 3rd edition, CAN/CSA-C22.2 No 60950-00 3rd edition, FCC part 15 - Class A, ICES-003, EN60950, EN55022-Class A, EN61000-6-2, VCCI, CCC

Related Products

Options and Accessories

- PCMCIA cards
- CompactFlash® cards
- Linear PCMCIA cards available 8 MB and 32 MB
- 64 MB On-Board Linear Flash Memory
- RFID Ready (110PAX4 only)
- WGLA through Swiss 721
- Firmware support for downloadable TrueType™ fonts
- PC memory card
- Additional fonts available

Zebralink Solutions

Software

- ZebraDesigner™ Pro
- ZebraDesigner for XML
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v 7.0
- Zebra Universal Driver
- ZBI-Developer™

Networking

- ZebraNet® 10/100 Print Server
- ZebraNet Internal Wireless Plus (available only in North America and the European Union)
- ZebraNet Wireless Plus

Firmware

- ZPL® II
- Global Printing
- XML-Enabled printing
- APL-1™/APL-D™ (Contact Zebra Development Services for additional details)
- Web View
- Alert
- ZBI 2.0™

Communications and Interface Capabilities

- High-speed bi-directional parallel interface, Centronics® compatible.
- High serial interfaces: RS-232C and RS422 with DB9F connector
- RS-485 multi-drop capability
- Configured baud rate (110 to 57.6 kB), parity, data bits, and stop bits
- Applicator interface with DB15F connector

Bar Code Symbolologies

Linear Bar Codes

Codabar, Code 11, Code 39, code 93, Code 128 with subsets A/B/C and UCC Case codes, EAN-8, EAN-13, Industrial 2-of-5, Interleaved 2-of-5, IBST-128, Logmars, MSI, Planet Code, Plessey, POSTNET, Standard 2-of-5, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions

2-Dimensional

Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF, PDF417, QR Code and TLC 39, Aztec

Fonts and Graphics

Fonts and Character Sets

- Bitmap fonts A through H and GS symbols are expandable up to 10 times, height and width independent
- Smooth scalable font Ø (CG Triumvirate™ Bold Condensed) is expandable dot-by-dot, height and width independent
- Sets: IBM® Code Page 850 International Characters
- Contains UFST® from Monotype Imaging, Inc.

Graphic Features

Supports user-defined fonts and graphics— including custom logos

* Specifications subject to change without notice. ©2010 ZIH Corp. ZebraLink, ZebraNet, Element Energy Equalizer, E³, ZBI 2.0, ZBI-Developer, ZebraDesigner, and all product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZebraNet, ZPL and ZPL II are registered trademarks of ZIH Corp. All rights reserved. CompactFlash is a registered trademark of SanDisk Corporation. TrueType is a trademark of Apple Computer, Inc. Centronics is a registered trademark of Centronics Data Computer Corporation. Windows is a trademark of Microsoft Corporation. CG Triumvirate is a trademark of Monotype Imaging, Inc. and may be registered in certain jurisdictions. IBM is a trademark or registered trademark of International Business Machines Corporation in the United States, other countries, or both. UFST is a registered trademark of Monotype Imaging, Inc. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners



www.zebra.com

Corporate Headquarters

+1 800 423 0442

E-mail: inquiry4@zebra.com

Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, Netherlands, Poland, Spain, Sweden

United Kingdom **Asia Pacific:** Australia, China, India, Japan, Portugal, South Korea **Latin America:** Argentina, Brazil, Florida (USA), Mexico GSA#: GS-35F-0268N

Africa/Middle East: Russia, South Africa, United Arab Emirates

Asia-Pacific Headquarters

+65 6858 0722

E-mail: apacchannelmarketing@zebra.com

EMEA Headquarters

+44 (0)1628 556000

E-mail: mseurope@zebra.com

Latin America Headquarters

+1 847 955 2283

E-mail: inquiry4@zebra.com

P1028475 R16 (6/10)