

PP 204

The Compact And Economical Matrix Printer For Logistics, Industry And Administration



The PP 204 provides for the economic access to professional dot matrix printing.

- Heavy Duty
24-wire dot matrix printer
- Compact, modern design
- High throughput
 - 400 cps (10 cpi)
 - 319 pages/hour
- 2 paper inputs for fanfold and cut sheet processing
- Up to 5 copies (1+4)
- Precise print positioning
- 9 scalable fonts
- Perfect barcode printing

TECHNICAL DATA

Printer Specification

Technology:	serial impact dot matrix
Printhead:	24 wires, 0.2 mm (0.01 inch) needle diameter; lifetime 400 million needle-strokes per wire.
Print mode	High Speed Draft (HSD), Draft Quality (DQ), Near Letter Quality (NLQ) and Letter Quality (LQ)
Print format:	80 columns at 10 cpi
Ribbon:	nylon ribbon cassette, black, more than 5 million characters
Dimensions:	415 x 330 x 120 mm (WxDxH) (16.3 x 13 x 4.72 inch)
Weight:	7.3 kg (16 lb)
Diagnostics:	selftest, hexdump
Operator Panel:	5 pushbutton, 2 modes, 6 LEDs indicators, 1 buzzer
Rated Voltage:	220 - 240 VAC ± 10% 50 - 60 Hz
Power consumption:	max. 180 W, Standby max. 10 W
Environmental conditions:	operating: + 5 to +38°C (+50 to +100° F) 30 to 80% rel. humidity storage: -15 to +60 °C (+5 to +140 ° F) 10 to 90% rel. humidity
Noise level:	max. 49 dB(A) acc. to ISO 7779
Agency approvals:	CE , TÜV

Performance

Print speed:	HSD:	400 cps at 10 cpi
	DQ:	360 cps at 10 cpi
	NLQ:	225 cps at 10 cpi
	LQ:	113 cps at 10 cpi
Throughput:	DQ:	319 pages/hour
	LQ:	172 pages/hour
Duty cycle:	8,000 pages per month	
MTBF:	20,000 hours at 25% duty cycle	

Paper Handling

Paper input:	Fanfold paper: push tractor with park position Cut sheet: Friction Feed, top in, top out
Paper output:	rear side, zero-tear-off
Paper weight:	Up to 280 g/m ²
Paper width:	Fanfold paper 102 to 267 mm (4.0 to 10.5 inch), Cut sheet 102 to 267 mm (4.0 to 10.5 inch)
Paper length:	Fanfold over 102 mm (4.0 inch) Cut sheet 76 to 364 mm (3.0 to 14.3 inch)
Form feed:	5,6 inch/second
Copies:	1 original + 4 copies; max. paper thickness 0.35 mm (0.01 inch)



Cut sheet printing with PP 204

Connectivity

Interfaces:	Parallel Centronics, USB
Emulations:	Epson ESC/P2 IBM Proprinter XL24 (AGM), Fujitsu DPL24C PLUS up to 128 KByte
Buffer:	up to 128 KByte
Character sets:	Italic character set Graphic character sets 1 and 2 IBM PS/2 character set, code page 437, 850, 852, 855, 860, 863, 865, 866 and DHN IBM 437 and 851 ISO 8859-1 and ECMA 94 61 national character sets
National character sets (all emulations.):	Code pages 437, 850, 851, 852, 855, 860, 862, 863, 865, 866, ISO 8859-1, ECMA 94, USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazovia 1 and 2, Polish 1 and 2, Latin 2 1 and 2, Latin P, PG-DHN, ELOT 927, Lithuanian 1 and 2, MIK, Macedonian, PG-MAC, ABY, ABG, DEC GR, GREEK 11, HBR-OLD, HBR-DEC, ISO Turkish, ISO Latin, Kamenicky 1 and 2, Turkish 1 and 2, ELOT 928, Cyrillic, RUSCII, Latin-9 (Note: Some national character sets do not support some resident fonts.)
Resident fonts:	Letter Quality - Bitmap fonts: Courier 10, Pica 10, Prestige Elite 12, Boldface PS, Compressed, Draft 12, High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10 - Scalable fonts: Courier (upright, italic, bold) Nimbus Sans (upright, italic, bold) Timeless (upright, italic, bold)
Character attributes:	Bold, shadow, double-width, double-height, condensed, superscript, subscript, underlining, justified and proportional. Other modes, such as italic, multi size, outlined, shaded, and overlay, are available depending on the emulation used.
Pitches:	10, 12, 15, 17.1, 18 und 20 characters/inch, proportional
Line spacing:	1, 2, 3, 4, 5, 6, 7 or 8 lines/inch
Barcodes:	Code 3 of 9, UPC-A, UPC-A with check character, Codabar (NW7), EAN13, EAN8, Industrial 2 of 5, Matrix 2 of 5, Interleaved 2 of 5, Code 128 max. 360 x 360 dpi
Graphics:	

Printer drivers for Windows 3.x/95/98/NT 4.0 /2000/XP are available for download at www.psiprinters.com.

Specifications are subject to change without notice.
All registered trademarks are the property of their respective companies.

PSi Printer Systems international GmbH
Eiserfelder Straße 316
D - 57080 Siegen
Tel: + 49 (0)271 / 3597 - 102 e-mail sales@psi-si.de
Fax: + 49 (0)271 / 3597 - 190 <http://www.psiprinters.com>

