

Zebra® Desktop Printers



High-quality desktop printers deliver unmatched reliability and versatility

Zebra's Desktop printer family offers a comprehensive choice of direct thermal (LP) and thermal transfer (TLP) models for 2- and 4-inch wide printing—each with distinctive characteristics to ensure your specific application is fully satisfied.

Small Size with No Compromise in Performance

Media loading is simplified thanks to the OpenACCESS™ design, which tucks the printhead into the printer's top cover, and provides a clear media window for easy monitoring. Just drop the media in, shut the cover, and start printing! Maximize workplace efficiency with a 5-inch media roll capacity (for fewer label roll changes) and a space-saving, compact design. Their durable, dual-wall construction ensures that Desktop series printers will withstand rough handling in your busy work environment.

Flexible Networking and Connectivity

For optimal integration in today's IT environments, select from serial, parallel, and USB interfaces. Zebra's ZPL II®-based desktop printers offer easy-to-use advanced printer management with ZebraNet™ Bridge Enterprise.

The Desktop series printers integrate easily into a variety of mid- to low-volume printing applications including:

- Shipping/Receiving
- Warehouse shelf labeling and inventory control
- Healthcare specimen labeling and patient tracking
- Retail product marking, shelf labeling, and coupon and receipt printing
- Transportation/Logistics ticket printing
- E-commerce postage

Zebra Desktop Printers

LP/TLP 2824 Plus™



The ultra-compact LP/TLP 2824 Plus bar code label printers bring powerful performance to applications requiring a space-saving printer and media widths of 2.2 inches/56 mm or less. They include a 32-bit RISC processor for faster formatting and first label out, an auto-sensing serial port, and co-resident EPL™ and ZPL® programming languages. Available options include additional memory, 10/100 Ethernet, label peeler, and receipt/label cutter.

Maximum Print Area

Width: 2.2"/56 mm
Length: 39.0"/990 mm

Print Speed

Maximum print speed 4"/102 mm per second

Resolution

203 dpi/8 dots per mm

Memory

Standard: 4 MB Flash, 8 MB SDRAM
Optional: 64 MB Flash with real-time clock for a total of 68 MB

Physical Characteristics

	LP 2824 Plus	TLP 2824 Plus
Width:	4.37"/111 mm	5.3"/135 mm
Depth:	8.5"/216 mm	9.5"/241 mm
Height:	6.75"/171 mm	7.0"/178 mm
Weight:	2.7 lbs./1.2 kg	3.5 lbs./1.6 kg
	(Weight of printer only; no media or options)	

Programming Languages

EPL and ZPL co-resident

Media Specifications

Label and liner width: 1"/25.4 mm to 2.36"/60 mm
Ribbon width (outside diameter):
1.33"/34 mm to 2.24"/57 mm (TLP only)
Ribbon length: 244/74 m (TLP only)

LP/TLP 2844™



Ideal for applications such as shipping and receiving, parcel delivery, warehouse management, retail, and healthcare, Zebra's space-saving LP/TLP 2844 printers offer efficient and reliable 4-inch-wide desktop labeling at an affordable price. These simple-to-operate, low-maintenance printers reduce training requirements and operating costs, and provide flexible solutions through a variety of options and accessories.

Maximum Print Area

Width: 4.09"/104 mm
Length in page mode:
11"/279 mm (with standard memory)
22"/558 mm (with optional memory)
Length in line mode: Unlimited (LP only)

Print Speed

Maximum print speed 4"/102 mm per second

Resolution

203 dpi/8 dots per mm

Memory

Standard: 512 KB Flash; 256 KB SRAM
Optional: 1 MB Flash; 512 KB SRAM

Physical Characteristics

	LP 2844	TLP 2844
Width:	7.6"/193 mm	7.8"/198 mm
Depth:	8.2"/208 mm	9.4"/238 mm
Height:	6.6"/168 mm	6.8"/173 mm
Weight:	3.2 lbs./1.5 kg	3.7 lbs./1.7 kg
	(Weight of printer only; no media or options)	

Programming Language

EPL

Media Specifications

Label and liner width: 1"/25.4 mm to 4.25"/108 mm
Ribbon width (outside diameter):
1.33"/33 mm to 4.3"/110 mm (TLP only)
Ribbon length: 244/74 m (TLP only)

TLP 3842™



The space-saving TLP 3842 desktop printer, for print widths up to 4 inches, adds high-resolution print capability to Zebra's popular and proven Desktop series. The TLP 3842's 300-dpi printhead enables high-quality, crisp, clear printing of two-dimensional bar codes, fine text, and complex graphics—ensuring high-density data on very small labels is easy to read and highly scannable.

Maximum Print Area

Width: 4.09"/104 mm
Length in page mode:
11"/279 mm (with standard memory)
22"/558 mm (with optional memory)

Print Speed

Maximum print speed 2"/51 mm per second

Resolution

300 dpi/12 dots per mm

Memory

Standard: 1 MB Flash; 512 KB SRAM
Optional: 1.2 MB SRAM

Physical Characteristics

Width: 7.8"/198 mm
Depth: 9.4"/238 mm
Height: 6.8"/173 mm
Weight: 3.7 lbs./1.7 kg
(Weight of printer only; no media or options)

Programming Language

EPL

Media Specifications

Label and liner width: 1"/25.4 mm to 4.25"/108 mm
Ribbon width (outside diameter):
1.33"/33 mm to 4.3"/110 mm
Ribbon length: 244/74 m

LP/TLP 2844-Z™



The LP/TLP 2844-Z printers bring powerful performance and exceptional versatility to the desktop class. Equipped with a 32-bit microprocessor for fast label processing and throughput, these 4-inch printers provide unparalleled productivity. They are based on ZPL II (Zebra Programming Language) for simplified label formatting and seamless integration where full-size Zebra printers are already installed.

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/990 mm (with standard memory)

Print Speed

Maximum print speed 4"/102 mm per second

Resolution

203 dpi/8 dots per mm

Memory

Standard: 8 MB SDRAM; 4 MB Flash
Optional: 8 MB Flash with real-time clock (12 MB total)

Physical Characteristics

	LP 2844-Z	TLP 2844-Z
Width:	7.6"/193 mm	7.8"/198 mm
Depth:	8.2"/208 mm	9.4"/238 mm
Height:	6.6"/168 mm	6.8"/173 mm
Weight:	3.2 lbs./1.5 kg	3.7 lbs./ 1.7 kg

(Weight of printer only; no media or options)

Programming Language

ZPL

Media Specifications

Label and liner width: 1"/25.4 mm to 4.25"/108 mm
Ribbon width (outside diameter):
1.33"/33 mm to 4.3"/110 mm (TLP only)
Ribbon length: 244/74 m

TLP 3844-Z™



The TLP 3844-Z's 300-dpi printhead enables high-quality, crisp, clear printing for labeling applications that require data such as two-dimensional bar codes, fine text, or complex graphics. Scanning and reading data on very small labels, for example laboratory vial labels or jewelry tags, is greatly enhanced.

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/990 mm (with standard memory)

Print Speed

Maximum print speed 4"/102 mm per second

Resolution

300 dpi/12 dots per mm

Memory

Standard: 8 MB SDRAM; 4 MB Flash
Optional: up to 8 MB Flash with real-time clock (12 MB total)

Physical Characteristics

Width: 7.8"/198 mm
Depth: 9.4"/238 mm
Height: 6.8"/173 mm
Weight: 3.7 lbs./ 1.7 kg
(Weight of printer only; no media or options)

Programming Language

ZPL

Media Specifications

Label and liner width: 1"/25.4 mm to 4.25"/108 mm
Ribbon width (outside diameter):
1.33"/33 mm to 4.3"/110 mm
Ribbon length: 244/74 m

TTP 2100™ Desktop Ticket Printer



The TTP 2100 direct thermal ticket printer is part of Zebra's kiosk printer family, which is specially designed to work in unattended, harsh environments where reliability, durability and minimal maintenance is critical. Using the same robust mechanism for attended applications, this compact desktop is ideal for ATB1 boarding passes, bag tags and tickets. The TTP 2100 includes high-end features such as retain or eject presenter, auto media loading, advance status reporting, print speeds up to 6"/150 mm per second and media thickness of up to .26 mm.

Maximum Print Area

Width: 3.1" (80 mm)
Length: 23.6" (600 mm)

Print Speed

Maximum print speed 6"/150 mm per second

Resolution

203 dpi/8 dots per mm

Memory

Standard: 8 MB SDRAM; 4 MB Flash
Optional: up to 8 MB Flash with real-time clock (12 MB total)

Physical Characteristics

Width: 4.5"/115 mm
Height: 3.1"/85 mm
Depth: 7.1"/137 mm
Weight: 3.1 lbs./1.4 kg
(weight of printer only; no media or options)

Programming Language

KPL

Media Specifications

Paper width: 2.13"/54 mm to 3.25"/82.5 mm
Maximum media roll size: 9.8"/250 mm
Media thickness:
0.004"/0.11 mm to 0.01"/0.26 mm for 2.13"/54 paper
0.004"/0.11 mm to 0.007"/0.19 mm for 3.25"/82.5 mm paper
Media types: Roll or fanfold stock or single-cut hand fed

Specifications at a Glance*

All LP/TLP 2800 & 3800 Series Models

Standard Features

- Print method: Direct thermal (LP) or direct thermal/thermal transfer (TLP)
- Construction: ABS double-walled casing
- OpenACCESS™ design
- Head up sensor
- Serial, parallel, and USB interfaces
- Windows® drivers (95, 98, NT v.4.0, 2000, XP)
- Windows printer utilities
- ZebraDesigner™ basic label design software

Operating Characteristics

Environmental

- Operating Temp: 40° F/5° C to 105° F/41° C
- Storage/Transport Environ. -40° F/-40° C to 140° F/60° C
- Operating Humidity 10–90% non-condensing
- Storage Humidity 5–95% non-condensing

Electrical

- Autoranging external power supply
- Input: 100–240 VAC; 50–60 Hz
- Output: 20 VDC; 2.5 A

Agency Approvals

UL-CUL, FCC, VCCI, C-TICK, CB, CE, CCC, NOM, IRAM, BSMI, GOST (Refer to technical specification for each individual product for further details.)

ZebraLink™ Solutions

Software

- ZebraDesigner (standard)
- ZebraDesigner Pro (option)
- ZebraNet™ Bridge Enterprise (standard)
 - Full printer management for ZPL printers
 - PrintServer management for EPL printers
- ZebraNet Utilities 7.0
 - PrintServer management for EPL and ZPL printers

Firmware

- EPL2™
- ZPL
- ZPL II®
- Web View
- Alert
- Zebra Setup Utilities (standard)

Communication and Interface Capabilities

- Serial RS-232 (DB9)
- Centronics® Parallel (36 pin)
- USB v 1.1

Fonts/Graphics/Symbologies

Fonts and Character Sets (EPL Desktop Series)

- Standard fonts: 5 bitmapped, expandable 8x
- Soft font storage in Flash memory

Fonts and Character Sets (ZPL Desktop Series)

- Standard fonts: 16 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
- Supports user-defined fonts and graphics—including custom logos
- IBM® Page 850 International Characters

Graphic Features

- Line and box drawing
- PCX graphic storage

Bar Code Symbologies

- **EPL models:** Linear bar codes: Code 39, Code 128A, B & C (User selectable/Auto), UCC/EAN-128, Code 93, Codabar, Interleaved 2-of-5, UPC-A, UPC-E, UPC-A with 2 and 5 add on, UPC-E with 2 and 5 add on, EAN 13, EAN 8, EAN 13 with 2 and 5 add on, EAN 8 with 2 and 5 add on, Postnet (5, 9, 11, & 13 digit) Japanese Postnet, Plessey (MSI-1), MSI-3, German Post Code, RSS-14 (limited, truncated, stacked) (downloadable)
 - 2-dimensional bar codes: MaxiCode (modes 2,3,4,6), PDF417, MacroPDF417, QR Code (optional—with Asian font set only), Data Matrix (downloadable)
- **ZPL models:** Linear bar codes: Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-of-5 digit extensions, Plessey, POSTNET, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, RSS-14 (limited, truncated, stacked)
 - 2-dimensional bar codes: PDF417, MicroPDF-417, Code 49, MaxiCode, Codablock

Options and Accessories

- Cutter
- Real-time clock
- Asian font set
- Media Adapter Guide kits (for printing narrow media—refer to tech specs for detail)
- Dispenser
- Keyboard Display Unit (KDU)¹
- Memory Expansion
- Liner-free platen (LP models only)
 - ¹ EPL products only. Check for ZPL compatibility availability.

TTP 2100 Series Models

Standard Features

- Direct thermal ticket printing for ATB1 boarding cards, bag tags, and other ticketing formats
- Retain or eject presenter
- Auto ticket loading does not waste tickets
- Various media mounting options give flexibility to kiosk design, up to 250 mm dia media rolls
- Paper guide available in 51, 54, 60, 66, 80, 82.5, and dual 54/82 mm
- USB or RS232 serial connectivity standard
- 203-dpi printing
- Windows drivers for plug and play
- Prints any font, code-page, bar code, and graphics supported by the operating system

Operating Characteristics

Environmental

- Operating Temp: 32 F/0 C to 122 F/50 C
- Storage Temp: 14 F/-10 C to 122 F/50 C
- Operating Humidity: 35% to 75% non-condensing
- Storage Humidity: 10% to 90% non-condensing excluding paper

Electrical

- 24Vdc +/-5% average 2A peak 6A

Communication and Interface Capabilities

- TTP 2110: RS232 serial interface
- TTP 2130: USB interface
- Operating system: Windows 2000, XP, Server 2003, and Linux

Fonts/Graphics/Symbologies

Bar Codes

- EAN 8, EAN 13, EAN128, UPC, Interleaved 2-of-5, ISBN, Code39, Code128, and 2-D PDF-417

Graphics

- Logotypes and b&w BMP-files

Standard fonts

- ATM9, OCR-B 10 and 12, up to 8 fonts can be uploaded
- Text attributes: Underline, bold, italics, reverse print, multiple width and height

Options and Accessories

- Print guides for 2"/51 mm, 2.1"/54 mm, 2.4"/60 mm, 2.6"/66 mm, 3.1"/80 mm and 3.3"/82.5 mm, and dual 2.1"/54 mm to 3.2"/82 media
- Media Holder TTP 2100 (includes quick fit hubs and spring)
- Output Tray
- Leaf spring retainer for quick-fit hubs
- Paper Low Sensor with 300 mm cable

*Specifications subject to change without notice.

©2010 ZIH Corp. ZebraLink, ZebraDesigner, EPL, EPL2, ZebraNet, OpenACCESS, and all product names and numbers are Zebra trademarks, and Zebra, ZebraNet, ZPL, and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Centronics is a registered trademark of Centronics Data Computer Corporation. CG Triumvirate is a trademark of Monotype Imaging, Inc. and may be registered in certain jurisdictions. IBM is a trademark or registered trademark of International Business Machines Corporation in the United States, other countries, or both. All other trademarks are the property of their respective owners.



www.zebra.com

Corporate Headquarters

+1 800 423 0442
E-mail: inquiry4@zebra.com

Asia-Pacific Headquarters

+65 6858 0722
E-mail: apacchannelmarketing@zebra.com

EMEA Headquarters

+44 (0)1628 556000
E-mail: mseurope@zebra.com

Latin America Headquarters

+1 847 955 2283
E-mail: inquiry4@zebra.com

Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, Netherlands, Poland, Spain, Sweden, United Kingdom
Asia Pacific: Australia, China, India, Japan, Singapore, South Korea **Latin America:** Argentina, Brazil, Florida (USA), Mexico **Africa/Middle East:** Russia, South Africa, United Arab Emirates