

PP 3034MICR

CONTINUOUS FORMS LASER PRINTER



PP 3034MICR with optional Stacker IPS 3034

The check printing system PP 3034MICR offers the highest level of security, accuracy and reliability. P*Si* Laser GmbH combines best-in-class MICR toner and software technology.

The result is a complete solution of check printing that meets industry standards.

Prints checks, payrolls, accounts, claims, lists for your customers. E13B and CMC7 fonts are already built-in which makes it very easy to use them in any of your MS-Windows based application.

If needed a paper stacker can be optionally attached to the PP 3034MICR which stacks up to 2,000 pages without user intervention.

- Ensures highest MICR printing quality using 600dpi laser print technology
- Prints the entire check in one pass including logo, customer data, MICR line and signature
- Integrated MICR Fonts for CMC7 and E13B
- Long life MICR toner
- Print speed of 90 checks/min
- Paper width up to 304.8 mm (12 inch)
- Accurate paper stacker without operator involvement (iPS 3034) up to 2,000 pages
- Network interface (Ethernet 10BaseT/100TX) and HP LaserJet Emulation (PCL5e)



PP 3034MICR

CONTINUOUS FORMS LASER PRINTER

Printer Specification

| | |
|----------------------------------|---|
| Print Speed: | up to 44 pages/ minute (Letter Landscape) up to 34 pages/ minute (11 inch page length) up to 31 pages/ minute (12 inch page Length) (2,270 lines/ minute at 6 lines/ inch) up to 90 checks/ minute |
| Resolution: | 600 x 600 dpi |
| Workload: | 50,000 pages per month |
| Print Method: | Electrophotographic by means of laser diode One-component toner/developer system Fusing by heat and pressure at adjustable temperature |
| Control Panel: | Two lines LCD display (16 characters per line); ONLINE, FORMFEED, MENU, CANCEL |
| Diagnostics: | Selftest, hexdump |
| Dimensions: | Printer 539 x 498 x 588 mm (W x H x D) |
| Weight: | 40 kg incl. imaging cartridge |
| Rated Voltage: | 100-110 V AC, 50-60 Hz 110-120 V AC, 50-60 Hz 220-240 V AC, 50-60 Hz |
| Max Current: | 12 A - 110 V 11 A - 120 V 6 A - 230 V |
| Power Consumption: | |
| Operating | < 800 W average (< 1,300 W max.) |
| Stand-by | < 110 W average (< 1,200 W max.) |
| Sleep | < 45 W average |
| Environmental Conditions: | |
| Operating | +10 to 35°C, 15 to 85 % rel. humidity |
| Storage Consumables | 0 to 35°C, 30 to 85 % rel. humidity |
| Sound Level: | 60 dB(A) operating |
| Lifetime: | up to 2,000,000 pages (Letter Landscape) |
| Approvals: | CE, VDE / GS, UL, C-UL, FCC |

Connectivity

STANDARD INTERFACES AND EMULATIONS

| | |
|--------------------------|--|
| Interfaces: | Parallel IEEE 1284, Ethernet 10BaseT/100BaseTX |
| Emulations / PDL: | HP LaserJet 4 (PCL 5e, PJL), HP - GL/2 PCL / PJL Extensions |
| Fonts: | 45 scalable fonts, 10 bitmap fonts |
| Barcodes: | Code 39, Code 93, Code 128, Codabar, 2/5 industrial, 2/5 interleaved, EAN 8/13 Add on 2/5, Postnet, MSI, UPC-A, UPC-E, KIX-Code, Datamatrix Code |

Optional data stream converter available for IPDS.

Paper Handling

| | |
|----------------------------|--|
| Type: | Continuous forms and labels with tractor pin holes |
| Paper Input: | from the front by means of tractor |
| Paper Output: | to the rear |
| Paper Width: | min. 101.6mm (4 inch), max. 304.8mm (12 inch) |
| Print Width: | max. 279.4mm (11 inch) |
| Page Length: | |
| Printer / iPS 3034: | min. 177.8 mm, max. 431.8 mm (7 to 17 inch) |
| Printer: | min. 76.2 mm, max. 508 mm (3 to 20 inch) |
| Paper Weight: | 64 g/m ² to 157 g/m ² |

Control Unit

| | |
|---------------------------------|--|
| Processor: | PowerPC |
| Data Memory: | 512 MB standard |
| Program and Font Memory: | 32 MB FLASH allows onsite software update |
| Stacker Control: | Supports attached intelligent Paper Stacker iPS 3034 |

Consumables

| | |
|--------------------------------|---|
| Imaging Cartridge MICR: | for Letter Format (8,5 x 11 inch) at 5% MICR - toner coverage up to 12,000 pages |
| Imaging Cartridge: | for Letter Format (8,5 x 11 inch) at 5% toner coverage up to 18,000 pages |
| Fusing Unit: | up to 500,000 pages (Letter Landscape) |
| Transfer Unit: | up to 150,000 pages (Letter Landscape) |

Options

| | |
|--------------------|--|
| iPS 3034: | Assures accurate stacking of forms up to 2,000 pages without operator involvement |
| Dimensions: | iPS: 512 x 1,192 x 1,113 mm (WxHxD) printer / iPS: 540 x 1,208 x 1,118 mm (WxHxD) |

Printer drivers for Windows and Linux are available.
Additionally, printer configuration software (Windows) Profiler and Profile
Selector and device types for SAP R/3 can be downloaded from the PSI website.

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation. Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.