





# Benefits of Our ODV-2D Printers





## Eliminate expensive compliance fees by producing 100% accurate barcodes, 100% of the time.

The ODV-2D is the industry's first affordable, fully integrated solution with the ability to print, verify, and validate 1D and 2D barcodes. The ODV-2D installs on either the T8000 or T6000e printers. It is the first system that grades barcodes to ISO 15415,15416 and 15426 standards and stores a detailed report of each transaction. Our exclusive technology reads each barcode, identifies a rejected barcode, and reprints a replacement label without operator intervention. The ODV-2D pays for itself by eliminating costly charge backs and fines for non-conforming labels. Advanced features allow it to integrate easily and quickly into existing applications.



### **Compliant Verification**

- Verifies full suite of 1D and 2D barcodes with up to 50 barcodes per label
- Performs both data validation and compliance verification
- Grades to ISO standards including Quiet Zone and Check Sum errors
- Label back up and overstrike to identify bad barcodes
- Barcode "GPS" dynamically locates barcodes on a label by label basis to improve throughput



### **Productivity**

- Prints and verifies at up to 8 ips ODV-2D can read 1D and 2D barcodes in any 90° orientation
- Print, verify, and encode RFID labels all in a single pass, exclusively on the T6000e
- PrintNet Enterprise Auto ID provides global or enterprise wide network access, control, update and reporting
- Compatible with third party label software through PXML data reporting
- Most extensive suite of printer emulations in the industry



#### **Dependable Design**

- Field kits available for both T8000 and T6000e printers
- Easy installation and setup
- Calibration check from printer's control panel using provided plague
- Works with a wide variety of label and ribbon types

# Tired of Rejected Shipments and Non-Compliance Fees?

With a global increase in regulatory compliance standards and fines, it is more important than ever to ensure your products are labeled correctly with accurate barcodes. ODV-2D addresses these requirements with the ability to validate and verify up to 50 barcodes per label including 2D barcodes.

The ODV-2D reads and grades every barcode on every label based on ISO standards. When ODV-2D rejects a barcode, it overstrikes the label and reprints it without operator intervention. At the end of the day you can generate a report directly from the printer with data on every label printed and graded.

### **Combining Verification with Validation**

The ODV-2D can verify and validate barcodes as they are printed. The data printed on the label is validated to match the data sent from the host (native commands only). The barcode image is verified to comply with the ISO standards.

# Print, Verify, and Encode RFID Labels All in A Single Pass

The upgraded T6000e with ODV-2D allows users to print and encode RFID labels and inspect and grade the quality of printed barcodes in a single pass. Now, one printer can now do the work of multiple devices to create a new level of productivity and cost savings. No longer are two separate machines needed to perform two completely different functions. This is a unique function not available on any other printer currently on the market.

# Manage Your Entire Enterprise from a Single Location

Printronix Auto ID Data Manager (part of the PrintNet Enterprise Suite) gives you the ability to dynamically record, archive and generate reports of scanned barcode data for every printer on your network. With the addition of our robust printer management tool, you can pull reports for your entire enterprise as well as monitor and configure printers from anywhere in the world. You can also designate events and be alerted to printer issues via email. PrintNet Enterprise is available at no charge.

### **Closed-Loop Application Design**

Printronix Auto ID's integration of ODV into the printer not only enables the printer to backup and overstrike bad labels without operator intervention, but provides the application access to the data from the ODV, including grading reports as well as label images. Data from ODV can be passed back to the application in .csv or PXML format, enabling the label software to not only send labels to the printer, but can check each label to ensure that the correct data was printed and the label barcodes grades were acceptable. This data can be captured, merged with the print job information, and an image of the label can be captured as well and also archived with the ODV grading report for future reference.

Software partners such as TEKLYNX already use this application connection to provide a close-loop label quality process.



Full Overstrike Example (T8000 ODV-2D)



Partial Overstrike Example (T6000e ODV-2D)



### **ODV-2D Series** | Data Sheet





| Model  | T8000 ODV-2D           | T6000e ODV-2D                               |
|--|------------------------|---|
| Print Speed (ips)                                      | 8 max speed            | 8 max speed                                 |
| Print Width (in)                                       | 4/6*                   | 4   |
| Print Resolution (dpi)                                 | 203/300                | 203/300/600                                 |
| Back-up and Overstrike                                 | 6 in                   | 1 in  |
| Max Barcodes per label                                 | 50                     | 50  |
| Maximum Label Length (in)                              | 24                     | 24  |
| Media Handling   | Tear/Peel/Cut          | Tear/Peel                                   |
| Dual Vision / RFID function                            | No                     | Yes   |
| Printer Footprint (L / W / H)                          | 22 x 11.7 x 13         | 22 x 10.9 x 12.3                            |
| Barcode 2D   | Datamatrix, QR, PDF417 | Datamatrix, QR, PDF417                      |
| Read Technology  | Camera                 | Camera                                      |
| ISO Compliance   | Yes                    | Yes   |
| Scan Resolution (mils)                                 | 2                      | 2   |
| Minimum X-Dimension 1D (mils)                          | 10                     | 10  |
| Minimum X-Dimension 2D (mils)                          | 10                     | 10  |
| Barcode Support  | 1D, 2D                 | 1D, 2D                                      |
| Barcode GPS  | Yes                    | Yes   |
| Barcode Orientation                                    | 0°, 90°, 180°, 270°    | 0°, 90°, 180°, 270°                         |
| OCR  | Perceptor PTXL         | No  |
| OCR Point Size   | 5pt                    | No  |
| OCR Fonts  | Arial                  | N/A   |
| Characters   | OCR Characters         | No  |
| OCV / Blemish Detect / Pattern Match / Duplicate Check | Perceptor PTXL         | No  |
| Output Reports   | Yes                    | Yes   |
| Remote Config / Mgmt                                   | Yes                    | Yes   |
| Data Report Capture                                    | Yes                    | Yes   |
| RFID Option  | N/A                    | UHF / RAIN (GS1 EPC Gen2 v2 / ISO 18000-63) |
| Cloud Database   | Perceptor PTXL         | No  |

<sup>\*</sup>Scan width = 4"

For more information on ODV or label quality inspection, please contact your local Printronix Auto ID sales representative.





 ${\sf Perceptor\,PTXL\,trademark\,is\,owned\,by\,InterVision\,Global\,Group\,I\,perceptor-ptxl.com}$ 



#### **Global Headquarters**

9F, No. 95, Minquan Road, Xindian District New Taipei City, Taiwan 231 Office: +886 2 2218 6789

#### **EMEA**

Georg-Wimmer-Ring 8b 85604 Zorneding, Germany Office: +49 8106 37979 000

#### **Americas**

3040 Saturn Street, Suite 200 Brea, CA 92821 U.S.A. Office: +1657 258 0808